

12K 2-POST LIFT



SPECIFICATIONS

Part Number	EELR738B
Lifting Capacity	12,000 lbs. 5442 kg
Overall Height	13'10"/14'7" 4216mm/4445mm
Ceiling Height Required	167"/176" 4242mm/4470mm
Floor to Overhead Switch	13'3½"/14'½" 4051mm/4280mm
Rise Height (Screw Pads Highest Position)	77¾" 1975mm
Screw Pad Height	5¼"/6¾" 133mm/171mm
Overall Width	139¾" 3550mm
Inside of Columns	115" 2921mm
Drive-Thru Clearance	103" 2616mm
Arm Reach (Min-Max)	27½"-54½" 699-1386mm
Lifting Capacity Per Arm	3,000 lbs. 1361 kg
Rise Time	84 seconds
Motor	2HP, Single Phase, 60Hz, 208/230V
Hydraulic Pressure at Cap.	2600 PSI
Bay Requirements	Height: 168"/180" 4267/4572mm Width: 168" 4267mm Depth: 288" 7315mm
Lift Approximate Weight	2,000 lbs. 907 kg
Lift Shipping Dimensions	Length: 132" 353mm Width: 26" 660mm Depth: 288" 7315mm

HOFMANN® 

SERVICE BAY SPECIFICATIONS

	HEIGHT: 14'/15' MINIMUM
	WIDTH: 14' RECOMMENDED
	DEPTH: 24' RECOMMENDED
	POWER: 208-230V, 1PH, 30A

 **CONCRETE:** 4" (101mm) thick, reinforced, free from cracks/seams, 3500+ psi (20.7MPa) & cured 28+ days

SERVICE BAY LAYOUT




Fig 1a - General Specifications




Fig 1b - Service Bay Layout

COMPATIBLE ACCESSORIES

Stack Adapter Kit	10315	
Electric Vehicle Footpad	EVFPK	
Heavy-Duty Footpad 12K	B12162S-12	
Standard Footpad	B2270	
GM® Truck Footpad Set	B2280PR	
Cab-Off Adapter	B2290	
Wheel Service Workstation	B99700	
Air/Electric Workstation	B10264A	

MANUAL PART NUMBERS

Lift	EELR537B-IOM
------	--------------

UNITED STATES | CANADA
800.225.5786

UPDATED 02/2026

HOFMANN-EQUIPMENT.COM