



15K 4-POST ALIGNMENT LIFT



SERVICE BAY SPECIFICATIONS




-  **HEIGHT:** 12' 6" MINIMUM
-  **WIDTH:** 18' RECOMMENDED
-  **DEPTH:** 24' RECOMMENDED
-  **POWER:** 230VAC, 1PH, 60HZ, 3HP 30AMP
-  **PSI:** 90-120 PSI | 6-8 BAR

 **CONCRETE:** 4" (101mm) thick, reinforced, free from cracks/seams, 3500+ psi (20.7MPa) & cured 28+ days - Anchor minimum embedment 3¾" (87mm)

SPECIFICATIONS

| | STANDARD LENGTH | EXTENDED LENGTH |
|-------------------------|--------------------------------------------------|---------------------------|
| 15K 15K extended | EELR706APKG | EELR708APKG |
| Max Capacity | 15,000 lbs. 6804 kg | |
| Configuration | Open Front | |
| Overall Length | 250¾" (6370mm) | 277" (7038mm) |
| Overall Width | Front: 142" 3607mm Rear: 141¾" 3600mm | |
| Inside Columns | Front: 120¾" 3067mm Rear: 125½" 3188mm | |
| Between Columns | 195" (4953mm) 222½" (5651mm) | |
| Height of Columns | 99¼" (2521mm) Front 98" (2489mm) Rear | |
| Height of Runways | 8" 203mm | |
| Width of Runways | 26" 660mm | |
| Width Between Runways | 40⅝" 1032mm | |
| Max/Min Wheelbase | 183"/89½" 4648/2273mm | 210½"/113" 5347/2870mm |
| Max 2 Wheel Alignment | 167¾" 4261mm | 195¼" 4959mm |
| Rise Height | 78" 1981mm | |
| Rise Time | 85 Seconds (approximate) | |
| Shipping Weight | 4,350~4550 lbs. 1973~2046 kg | |
| Bay Height Requirements | 150" 3810mm | |
| Bay Width Requirements | Optimum: 216" 5486mm Minimum: 168" 4267mm | |
| Bay Depth Requirements | 290"-312" 7366-7925mm | |

STANDARD ACCESSORIES

| | | |
|------------------------------------------------|-------------|---------------------------------------------------------------------------------------|
| Jack Beam / w 2 - 3" and 2 - 6" stack adapters | EELS905A |  |
| 1 Pair Premium Turn Plate | EAK0289J06A |  |
| 2 Sets Rollback Paddles | EAK0277J28A |  |

JACK SPECIFICATION

EELS905A - 7,500 LBS. (3420KG)

| | |
|------------------------------------|------------------|
| Min. Arm Reach | 35 7/16" 900mm |
| Max. Arm Reach | 57 1/8" 1450mm |
| Min. Drive Over Height | 1½" 38.6mm |
| Min. Pad Height Arm Ext. Over Deck | 2 9/16" 65mm |
| Min. Lowered Height | ¾" 19mm |
| Max. Raised Height | 16½" 419.6mm |

VERSIONS

| | |
|----------------------------------------|--------------|
| Extended length | EELR708APKG |
| Extended length - Lights & Locking Kit | EELR708LLPKG |
| Standard length | EELR706APKG |
| Standard length - Lights & Locking Kit | EELR706LLPKG |

MANUAL PART NUMBERS

| | |
|------|-------------|
| Lift | EAZ0080V62A |
| Jack | EAZ0080V72A |