

# 16K 2-POST LIFT



## SPECIFICATIONS

16k   16k Extended Height	EELS743A	EELS744A
Lifting Capacity	16,000 lbs.   7257 kg	
Lift Configuration	Symmetric	
Arm Configuration	3-Stage Front & Rear	
Max Load Per Arm	4,000 lbs.	
Rise Height	Min. 75½"   Max. 81½" (w/stack adapters)	
Overall Height Options	13'6"   14'   14'6"	15'6"   16'   16'6"
Overall Width Options	12' 10¾"   +6" - 13' 4¾"   +12" - 13' 10¾"	
Floor to Overhead Switch	12'11"   13'5"   13'11"	14'11"   15'5"   15'11"
Arm Reach	Min 36¾"   Max 75"	
Screw Pad Height	Min 4¾"   Max 6½"	
Between Columns	10'   +6" - 10'6"   +12" - 11'	
Rise Time	62 Seconds	
Min. Ceiling Height Req.	13'8"   14'2"   14'8"	15'8"   16'2"   16'8"
ALI Certified	Yes	

## MANUAL PART NUMBERS

Lift	EAZ0080V84A
------	-------------

## SERVICE BAY SPECIFICATIONS

-  **HEIGHT:** 13' 6"/16' 8" MINIMUM
-  **WIDTH:** 16' RECOMMENDED
-  **DEPTH:** 28' RECOMMENDED
-  **POWER:** 208-230V, 1PH, 30A

 **CONCRETE:** 4" thick, reinforced, free from cracks/seams, 3500+ psi & cured 28+ days

## SERVICE BAY LAYOUT

