

20K 2-POST LIFT



SPECIFICATIONS


	STANDARD	EXTENDED
20k 20k Extended Height	EELS745A	EELS746A
Lifting Capacity	20,000 lbs. 9,072 kg	
Lift Configuration	Symmetric	
Arm Configuration	2-Stage Front & Rear	
Max Load Per Arm	5,000 lbs.	
Rise Height	Min. 76 ⁹ / ₁₆ " Max. 84 ⁹ / ₁₆ " (w/stack adapters)	
Overall Height Options	13'6" 14' 14'6"	15'6" 16' 16'6"
Overall Width Options	12' 10 ³ / ₄ " +6" - 13' 4 ³ / ₄ " +12" - 13' 10 ³ / ₄ "	
Floor to Overhead Switch	12'11" 13'5" 13'11"	14'11" 15'5" 15'11"
Arm Reach	Min 38 ¹ / ₂ " Max 62"	
Screw Pad Height	Min 6 ³ / ₁₆ " Max 7 ⁹ / ₁₆ "	
Between Columns	10' +6" - 10' 6" +12" - 11'	
Rise Time	62 Seconds	
Min. Ceiling Height Req.	13'8" 14'2" 14'8"	15'8" 16'2" 16'8"
ALI Certified	Yes	

MANUAL PART NUMBERS

Lift	EAZ0080V85A
------	-------------

SERVICE BAY SPECIFICATIONS

-  **HEIGHT:** 13' 6"/16' 8" MINIMUM
-  **WIDTH:** 16' RECOMMENDED
-  **DEPTH:** 28' RECOMMENDED
-  **POWER:** 208-230V, 1PH, 30A

 **CONCRETE:** 4" thick, reinforced, free from cracks/seams, 3500+ psi & cured 28+ days

SERVICE BAY LAYOUT

