

# 16K 2-POST





**SERVICE LIFT** 

ENGINEERING UNLEASHED™

### 16K 2-POST

## ENHANCED EFFICIENCY SUPERIOR PERFORMANCE

The Hofmann® 16k 2-Post lift offers an impressive lifting capability of up to 16,000 pounds, empowering technicians to effortlessly elevate even the most substantial vehicles. Its engineering prowess distinguishes the 16k 2-Post lift as an indispensable resource for shops that routinely undertake the maintenance and servicing of large or heavy-duty vehicles.



#### THREE-STAGE FRONT & REAR ARMS

With our user-friendly three-stage front and rear arms, you can accommodate a wide range of vehicles, increasing shop efficiency.



#### **LOW-PROFILE URETHANE PADS**

With minimal maintenance required, low-profile urethane pads are designed for durability and longevity, accommodating a variety of lifting points recommended by OEMs.



#### VERSATILE INSTALLATION OPTIONS

Installation options are convenient and versatile, with three height and width choices: 13.5', 14', or 14.5' height installation, and 10', 10.5', or 11' width installation.



#### ADJUSTABLE HEIGHT EXTENSION

Facilitating the efficient handling of higher-profile vehicles, the adjustable column height maximizes workspace under vehicles for increased service capability and technician safety.



#### AIR & ELECTRIC WORKSTATION (OPTIONAL)

Provides electricity and air mounted directly to the lift column for ultimate convenience for technicians.

TECHNICAL SPECIFICATIONS	
Part Number	Standard: EELS743A Extended: EELS744A
Lifting Capacity	16,000 lbs.   7,257 kg
Configuration	Symmetric
Overall Width	155"/161"/167"   394/409/424cm
Overall Height	Standard: 162"/168"/174"   411/427/442cm Extended: 186"/192"/198"   472/488/503cm
Max Lifting Height	76"-82"   193-208cm
Lifting Time	62 seconds
Power Requirements	208-230V 60Hz 3HP   2.2kW
Air Supply Required	90-120 PSI   6-8 BAR
Minimum Recommended Bay Size (WxL)	15'x28'   457x853cm

#### STANDARD ACCESSORIES

3" & 6" Stack Adapters and Organizer Racks

#### **OPTIONAL ACCESSORIES**

Reducer bushing (set of 4) (10317), Air/Electric Workstation w/Filter/Lubrication/Regulator (EAK0299T27A), 3 Phase 230V (AD-81795) 1' Extension (12310-0), 2' Extension (12310-2)



US 800.251.4500

CANADA 800.267.2185



