

12K 2-POST



SERVICE LIFT

ENGINEERING UNLEASHED™

12K 2-POST

ENHANCED EFFICIENCY SUPERIOR PERFORMANCE

The Hofmann® 12k 2-Post lift offers a multitude of exceptional features that include symmetrical lifting capabilities, extended reaching front and rear arms, adjustable insert screw lifting pads and a cushioned overhead shut-off bar. With the potential for augmenting its functionality with a range of optional accessories, the 12k 2-Post lift presents the opportunity to effectively boost shop productivity even further.



INCREASED CAPACITY FOR LARGER VEHICLES

Providing up to two additional feet of workspace, this unit enables technicians to handle taller vehicles, including large trucks, SUVs, and cargo vans.



ADJUSTABLE HEIGHT EXTENSION

Facilitating the efficient handling of higherprofile vehicles, the adjustable column height maximizes workspace under vehicles for increased service capability and technician safety.



ADJUSTABLE URETHANE SCREW PADS

Heavy-duty polyurethane lifting pads with adjustable urethane screw facilitate quick and easy vehicle setup and include a telescoping feature that enables convenient access to factory-recommended lift points.



TWO-STAGE FRONT & REAR ARMS

Heavy-duty two-stage front and rear arms facilitate easy symmetric lifting across a wide range of vehicles.

TECHNICAL SPECIFICATIONS	
Part Number	EELR738A
Lifting Capacity	12,000 lbs. 5,443 kg
Configuration	Symmetric
Overall Width	140" 356cm
Overall Height	Standard: 166"-175" 421-445cm Extended: 190"-199" 483-505cm
Max Lifting Height	78" 198cm
Lifting Time	61 seconds
Power Requirements	208-230V 60Hz 1Ph 30A 2HP 1.5kW
Air Supply Required	90-120 PSI 6-8 BAR
Minimum Recommended Bay Size (WxL)	14'x24' 427x732cm

OPTIONAL ACCESSORIES

Extension Adapter Kit: 3" x4 / 6" x2 (EAK0299T22A)
24" Column Height Extension Kit (EAK0299T44B)
Electric Vehicle (EV) Footpad Adapter (TFPK)
Wide Frame Footpad Adapter (CHB2270)
Air/Electric Workstation w/Filter/Lubrication/Regulator (EAK0299T27A)
3 Phase 230V (EAK0299T45A / AD-9367)







