

10K 2-POST



SERVICE LIFT

 $\textbf{ENGINEERING UNLEASHED}^{\text{TM}}$

ENHANCED EFFICIENCY SUPERIOR PERFORMANCE

The Hofmann® 10k 2-Post automotive/general purpose lift features robust industrial-grade columns, plated arm pins, steel pulleys and other components engineered for longevity. It offers the added advantage of being able to handle vehicles in both symmetric and asymmetric configurations, illustrating its remarkable versatility and adaptability to a wide array of automotive service opportunities.



THREE-STAGE ASYMMETRIC FRONT ARMS & TWO-STAGE REAR ARMS

Elevate vehicles with confidence and precision, utilizing our three-stage, asymmetrical front arms, designed for effortless operation and impeccable weight distribution. Our two-stage rear arms seamlessly attach to the lifting points at the rear of the vehicle.







ADJUSTABLE HEIGHT EXTENSION

Facilitating the efficient handling of higher profile vehicles, the adjustable column height maximizes workspace under vehicles for increased service capability and technician safety.

FAST RISE TIME

Minimize the time spent lifting vehicles, and speed up the whole process with industry leading rise times.

ADJUSTABLE URETHANE SCREW PADS

Heavy-duty polyurethane lifting pads with adjustable urethane screw facilitate quick and easy vehicle setup and include a telescoping feature that enables convenient access to factory-recommended lift points.

TECHNICAL SPECIFICATIONS	
Air Supply Required	90-120 PSI 6-8 BAR
Configuration	Assymmetric
Lifting Capacity	10,000 lbs. 4,536kg
Lifting Time	40 seconds
Minimum Recommended Bay Size WxL	14'x 24' 427x732cm
Overall Height Standard	138"-148" 335cm
Power Supply	208-230V 60Hz 1Ph 20A 2HP 1.5kW



FIND A DISTRIBUTOR

https://hofmann-equipment.com/la-en/distributor





