

PRECISION WHEEL ALIGNMENT

ENGINEERING UNLEASHED™

geoliner® 630

REDUCE SETUP AND MEASUREMENT TIMES

Utilising advanced imaging technology, the Hofmann® geoliner® 630 provides accurate, real-time measurements, reducing setup and measurement times while generating serious productivity benefits. Equipped with our latest software, the geoliner® 630 wheel aligner provides readings to technicians in a matter of minutes.

NOTIFICATION SYSTEM

Our smart notification system maximises efficiency and accuracy by automatically identifying and fixing issues like suspension stress or environmental errors, and only requires technician intervention when more information is needed to take different corrective action.



COMPENSATE:

Measurement ok and compensated with no notification



WARN:

Wheel imperfections are compensated and user is warned



ALFRT:

Critical errors are detected and corrective actions are displayed

XD CAMERA TECHNOLOGY

Cutting-edge high-definition video speed cameras continuously monitor the alignment process and instantly detect common environmental conditions or vehicle issues with the potential to cause misalignment.

REMOTE-CONTROLLED TILT BEAM

Enables technicians to conveniently tilt the beam swiftly and with ease using a simple-to-operate remote control.

QUICK COMPENSATION


AND OPTIMISED ALIGNMENT FLOW

Boost productivity by eliminating unnecessary steps. The alignment process is greatly enhanced by our quick measurement compensation and optimised alignment flow, which enables shops to grow their alignment business through increased productivity.

MIDON

Using simple, easy-to-follow red and green LED lights,

our patented Vehicle **Orientation Directional Indicator** (VODI™) leads technicians through the measuring procedure while the monitor is not in view, decreasing the time spent moving back and forth between vehicle and aligner.





AC200 Clamps (EAK0350J80A)



Alignment Stand (RB24)

TECHNICAL SPECIFICATIONS	
Track Width	48"-96" 122-244cm
Wheelbase	79"-180" 201-457cm
Rim Size - AC200	12-24" 30-61cm
Power Supply	120/230V 1Ph 50/60Hz

STANDARD ACCESSORIES	
AC200 Wheel Clamps & Targets	Brake Pedal Depressor
Steering Wheel Holder	Two Wheel Chocks

FRANCE **GERMANY** FIND A DISTRIBUTOR AUSTRIA ITALY +43 2641 24524 +33 134 48 58 78 +49 8634 622 0 +39 0522 733 411





