

geoliner® 320



PRECISION WHEEL ALIGNER

ENGINEERING UNLEASHED™

PORTABLE ON-CAR 3D WHEEL ALIGNER

Due to its mobile, compact design that eliminates alignment space barriers, the Hofmann® geoliner® 320 allows technicians to complete fast, accurate wheel alignments in a smaller area.

The geoliner® 320 also comes with the software and features found in our conventional cross-beam alignment systems, so productivity is enhanced, while taking up less space to perform the alignment.

With the geoliner® 320, shops have a flexible alignment solution for precision service in a limited space, due to lift-mounted reference pods, camera pods and XD wheel targets. Our exclusive quick-release clamps attach to almost any variety of lift, and the geoliner® 320 requires no room in front of the lift to perform services.





ON-CAR SYSTEM

Cordless pods attach directly to the tyres using a wireless communication system with Bluetooth connectivity, delivering the highest degree of flexibility and mobility.



LIGHTWEIGHT AND DURABLE MAGNESIUM PODS

Designed to withstand rigorous use, the revolutionary balancing weight feature keeps these impact-resistant pods level at all times.



COMPLETELY MOBILE

With a versatile console that serves as both a viewing and charging station, you can move the unit throughout your shop with ease.

PROFITS GROW AS SERVICE OPPORTUNITIES ARISE.

VODITM

Easy-to-follow red and green LED lights, leads technicians through the measuring procedure while the monitor is not in view, decreasing the time spent moving back and forth between vehicle and aligner.





RECHARGEABLE BATTERIES

Built right into the cart, the innovative battery charger houses the batteries, charging them continuously when not in operation, so they are always primed for performance



OPTIONAL SECONDARY SCREEN

Have access to all the readings from anywhere in the shop. *Tablet not included

NOTIFICATION SYSTEM

Our smart notification system maximizes efficiency and accuracy by automatically identifying and fixing issues like suspension stress or environmental errors, which only requires a technician's intervention when more information is needed to take different corrective action.



COMPENSATE:

Measurement ok and compensated with no notification



WARN:

Wheel imperfections are compensated and user is warned



ALERT:

Critical errors are detected and corrective actions are displayed



AC700 CLAMPS



With a lightweight and durable design, AC700 clamps have the capacity to easily accommodate rims that range from 11"-22".

| TECHNICAL SPECIFICATIONS | |
|--------------------------|----------------------|
| Power supply | 110-240V 50/60Hz |
| Track Width | 48"-96" 122-244cm |
| Wheel Diameter (AC200) | 12"-24" 30-61cm |
| Wheelbase | 60"-180" 152-457cm |

RIDE HEIGHT MEASUREMENT



Eliminate manual data entry, speed up measuring, and increase accuracy using our specially designed, optional Ride Height Targets.

| STANDARD ACCESSORIES | |
|-----------------------|-----------------------|
| Two Wheel Chocks | Brake Pedal Depressor |
| Steering Wheel Holder | |



FIND A DISTRIBUTOR

https://hofmann-equipment.com/la-en/distributor

LATIN AMERICA



