

# *geodyna®* 7300P



**CAR WHEEL BALANCER**

**ENGINEERING UNLEASHED™**

A semi-automatic powerhouse, the geodyna® 7300P wheel balancer is ready to tackle any task with unmatched efficiency. The easyWeight™ technology employs a pinpoint laser for accurate adhesive weight placement. Its dual 3-digit LED display shows weight readings and positions, integrated into a redesigned ergonomic weight tray. For ease of use, it includes semi-automatic input for rim dimensions via 2D SAPE and smartSonar™, with easyALU™ for balancing mode selection.

## MONITOR AND INTEGRATED TOUCHPAD

This system features a raised monitor and integrated touchpad, providing convenient control, optimising workflow and simplifying the balancing process.

## QUICKBAL™

Engineered for optimal performance, this feature intelligently adjusts the number of revolutions according to each wheel's specifications. Operating at maximum speed, it effectively reduces cycle time, delivering swift and efficient results.



## EASYWEIGHT™

Laser technology precisely indicates the exact location for weight application. Not available for version 7300S.



## SEMI-AUTOMATIC DATA ENTRY

With intuitive gauge arm and easyALU™ technology, the system lets technicians touch the rim, automatically logging dimensions and selecting the correct weight-balancing mode.



## SMARTSONAR™

This intelligent system utilises sonar sensors to automatically detect the rim width, eliminating the need for manual input and reducing the possibility of errors. By streamlining the process, it enhances efficiency and accuracy.



## SPLIT WEIGHT MODE

This feature ensures accurate balancing and discreet weight concealment behind spokes, maintaining the wheel's aesthetic appeal and visual presentation.



## POWER CLAMP™

Consistently and reliably secures the wheel with a constant force ensuring exceptional accuracy and repeatable results. Only for version 7300P.

## TECHNICAL SPECIFICATIONS

Semi-Automatic Rim Diameter Range	8" - 25"   20 - 63,5cm
Semi-Automatic Width Range	3" - 15"   7,6 - 38cm
Manual Rim Diameter Range	8" - 32"   20 - 81,2cm
Manual Rim Width Range	1" - 20"   2,54 - 50,8cm
Max Wheel Diameter	42"   106,6cm
Max Wheel Weight	154 lbs.   70kg
Power Supply	230V 1ph 50-60Hz
Dimensions HxWxL	72"x35"x54"   183x88x138cm

## STANDARD ACCESSORIES

Integrated flange with quick-clamping nut, mechanical main shaft lock  
P models with conical flange, electro-mechanical Power Clamp™ device and electro-mechanical main shaft lock  
Drum, drum cushion, 3 cones (1,7-3,2" | 42-80mm), (2,8-3,9" | 72-99mm), (3,8-4,6" | 96-116mm) dia.  
Universal weight pliers, adhesive weight removing tool  
4 Storage pegs on left-hand side of machine

## VERSION DIFFERENCES

7300p - All features  
7300i - No Power Clamp™  
7300s - No Power Clamp™, no easyWEIGHT™

## FIND A DISTRIBUTOR

AUSTRIA  
+43 2641 24524

FRANCE  
+33 134 48 58 78

GERMANY  
+49 8671 96200 0

ITALY  
+39 0522 733 411



Snap-on® Total Shop Solutions offers a wide range of garage equipment solutions for workshops, garages, car dealers and tyre shops, thanks to the specific solutions provided by its portfolio of premium brands. Hofmann® is a brand of TSS and is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2025 Snap-on Incorporated. Hofmann® is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. sswb23018a (EU en) 8/2025

