

# geodyna® 7200S



**CAR WHEEL BALANCER**

**ENGINEERING UNLEASHED™**



Designed for various shop sizes, the geodyna® 7200S wheel balancing system combines precision with a compact design. User-friendly interface and vibrant elevated monitor allow technicians to balance wheels quickly and accurately. Within seconds, the display pinpoints imbalance and suggests weight placement. A rapid spin cycle offers speed and accurate measurements. Features like smartSonar™ and easyALU™ enhance efficiency throughout the balancing process. The geodyna® 7200 merges practicality with advanced features, ensuring profitable in-house wheel services in a small footprint.



## MONITOR AND INTEGRATED TOUCHPAD

This system features a raised monitor and integrated touchpad, providing convenient control, optimising workflow and simplifying the balancing process.

## QUICKBAL™

Engineered for optimal performance, this feature intelligently adjusts the number of revolutions according to each wheel's specifications. Operating at maximum speed, it effectively reduces cycle time, delivering swift and efficient results.

## TECHNICAL SPECIFICATIONS

Semi-Automatic Rim Diameter Range	8" - 25"   20 - 63,5cm
Semi-Automatic Width Range	3" - 15"   7,6 - 38cm
Manual Rim Diameter Range	8" - 32"   20 - 81,2cm
Manual Rim Width Range	1" - 20"   2.54 - 50,8cm
Max Wheel Diameter	42"   106.6cm
Max Wheel Weight	154 lbs.   70kg
Power Supply	230V 1ph 50-60Hz
Dimensions HxWxL	72"x31"x40"   183x78x101cm



## SEMI-AUTOMATIC


### DATA ENTRY

Intuitive gauge arm and easyALU™ technology, the system lets technicians touch the rim, automatically logging dimensions and selecting the correct weight-balancing mode.



## SMARTSONAR™

This intelligent system utilises sonar sensors to automatically detect the rim width, eliminating the need for manual input and reducing the possibility of errors. By streamlining the process, it enhances efficiency and accuracy. Only for 7200S.



## SPLIT WEIGHT MODE

This feature ensures accurate balancing and discreet weight concealment behind spokes, maintaining the wheel's aesthetic appeal and visual presentation.



## QUICK NUT CLAMP

An easy-to-use manual clamping device that allows a secure attachment of the wheel to the balancer shaft.

## STANDARD ACCESSORIES

- Integrated flange with quick-clamping nut
- Drum, drum cushion, 3 cones (1,7-3,2" | 42-80mm), (2,8-3,9" | 72-99mm), (3,8-4,6" | 96-116mm) dia.
- Universal weight pliers, adhesive weight removing tool
- Rim width callipers (WB without smartSonar™ only)
- 4 Storage pegs on left-hand side of machine
- Wheel guard

## VERSION DIFFERENCES

- 7200S - All features
- 7200 - No smartSonar™

FIND A DISTRIBUTOR

AUSTRIA  
+43 2641 24524

FRANCE  
+33 134 48 58 78

GERMANY  
+49 8671 96200 0

ITALY  
+39 0522 733 411


Snap-on® Total Shop Solutions offers a wide range of garage equipment solutions for workshops, garages, car dealers and tyre shops, thanks to the specific solutions provided by its portfolio of premium brands. Hofmann® is a brand of TSS and is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2025 Snap-on Incorporated. Hofmann® is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. sswb23019a (EU en) 8/2025



HOFMANN-EQUIPMENT.COM

HOFMANN®