

**HOFMANN®** 

**geodyna® 4800-2L**



**TRUCK WHEEL BALANCER**

**ENGINEERING UNLEASHED™**

## TRUCK WHEEL BALANCER WITH MONITOR

The geodyna® 4800L is a highly-productive off-the-truck wheel balancer with a number of advanced functionalities, including a semi-automatic entry system for rim width input, an electronic friction brake for secure wheel positioning, split weight mode for adhesive weight placement, hidden weight mode, and patented optimisation mode. It also features a cone adaptor with a spacer and cone specifically designed for light-truck wheel balancing.

## RAISED MONITOR AND TOUCHPAD



Raised monitor and touchpad for convenient operational control.

## HEAVY-DUTY WHEEL LIFT



This lift helps facilitate the clamping of heavy truck wheels and offers ample storage space for cones, centring stars, and wing nuts.

## SEMI-AUTOMATIC DATA ENTRY



Technicians simply touch the rim with the gauge arm, and the system automatically enters the rim dimensions and selects the appropriate weight-balancing mode.

## SPLIT WEIGHT MODE



Accurate balancing and discreet weight concealment behind spokes, maintaining the wheel's aesthetic appeal and visual presentation.

## WEIGHT TRAY



The weight tray offers multiple housings for weights and also for the weight pliers.

### TECHNICAL SPECIFICATIONS

Semi-Automatic Rim Diameter Range	8"-26"   20-66cm
Semi-Automatic Width Range	2"-20"   5-51cm
Max Wheel Diameter	51"   130cm
Max Wheel Weight	550 lbs.   250kg
Power Supply	230V 1ph 50-60Hz
Dimensions HxWxL	79"x57"x54"   200x145x137cm

### STANDARD ACCESSORIES

Truck wheel cone adaptor with wing nut, light-truck cone of 4.8-6.8" | 122-172mm dia. & spacer  
Pneumatic wheel lift up to 250kg  
Storage pegs on left-hand side of the machine  
Wheel guard

### FIND A DISTRIBUTOR

AUSTRIA  
+43 2641 24524

FRANCE  
+33 134 48 58 78

GERMANY  
+49 8671 96200 0

ITALY  
+39 0522 733 411

