

SWING-ARM TIRE CHANGER

The monty® 1575 facilitates efficient in-house tire services without compromising safety. It effortlessly handles a variety of tire sizes and wheel configurations, while our patented twin cylinders drive self-centering clamping jaws, securing heavy-duty wheels and minimizing damage risk.

RIM CLAMPING BEAD SEATER



A direct burst of compressed air comes through the clamping jaws to facilitate bead seating.

COLUMN-INTEGRATED AIR TANK



An unobtrusive, vertical design, column-integrated air tank helps conserve valuable shop space with a large volume for increased blasting capabilities.

PRESSURE GAUGE



Positioned in an easy-to-see location, it serves to calibrate tires with high precision.

TECHNICAL SPECIFICATIONS Part Number (US) MONTY1575B Part Number (CA) EEWH790AUA Max Rim Diameter 24" | 61cm Max Tire Width 13" | 33cm Max Rim Width 12" | 31cm Max Wheel Diameter 40" | 101cm 115V 1Ph 60Hz Power Supply Air Pressure Required 116-174 PSI | 8-12 bar 72"x47"x44" | 182x119x112cm Dimensions HxWxD

TIRE CHANGER FOR GENERAL REPAIR SHOPS

ADJUSTABLE CLAMPING JAWS



To safeguard the wheel's integrity, these nylon-covered jaws are self-centering and grip the wheel firmly for elevated stability and safety.

SWING-ARM



Optimization of space is skillfully ensured with a mounting arm that pivots to the side, allowing the machine to be efficiently installed directly adjacent to a wall.

ON-FLOOR BEAD BREAKER



A conventional side-shovel bead breaker, featuring an ergonomically positioned pedal control situated a small distance from the shovel, is the quickest solution for efficiently handling a range of tires.

STANDARD ACCESSORIES

- Tire Lever
- Lube Bucket
- Lube Brush
- Protective Insert for Mount/Demount Head
- Plastic Jaw Protector



US 800.251.4500

CANADA 800.267.2185



