

## monty<sup>®</sup> 1620

The Hofmann® monty® 1620 tire changer is a versatile solution designed to handle intricate wheel and tire configurations in contemporary vehicles. It incorporates features like an ergonomic pedal-operated bead breaker, nylon-covered clamping jaws, and twin cylinders to ensure the secure positioning of wheels and prevent potential damage.

# TIRE CHANGER FOR GENERAL REPAIR SHOPS

### RIM CLAMPING BEAD SEATER



A direct burst of compressed air comes through the clamping jaws to facilitate bead seating.

### **ON-FLOOR BEAD BREAKER**



A conventional side-shovel bead breaker, featuring an ergonomically positioned pedal control situated a small distance from the shovel, is the quickest solution for efficiently handling a range of tires.

### **FIXED JAWS**



To safeguard the wheel's integrity, these nylon-covered jaws are self-centering and grip the wheel firmly for elevated stability and safety.

### **SWING-ARM**



Optimization of space is skillfully ensured with a mounting arm that pivots to the side, allowing the machine to be efficiently installed directly adjacent to a wall.

### PRESSURE GAUGE



**TECHNICAL SPECIFICATIONS** 

Positioned in an easy-to-see location, it serves to calibrate tires with high precision.

### **COLUMN-INTEGRATED AIR TANK**



An unobtrusive, vertical design, column-integrated air tank helps conserve valuable shop space with a large volume for increased blasting capabilities.

## Part Number MONTY1620B Max Rim Diameter 20" | 50.8cm Max Tire Width 15" | 38cm Max Rim Width 14" | 36cm Max Wheel Diameter 50" | 127cm Power Supply 115V 1Ph 60Hz

### STANDARD ACCESSORIES

- · Wave Plus Tire Lever
- Lube Bucket
- · Lube Brush
- Protective Insert for Mount/Demount Head
- Plastic Jaw Protector



Air Pressure Required

Dimensions HxWxD

US 800.251.4500

68"x47"x49" | 172x119x124cm

116-174 PSI | 8-12 bar

CANADA 800.267.2185



