



TILT-BACK TIRE CHANGER

ENGINEERING UNLEASHED™

PNEUMATIC TILT BACK TIRE CHANGER

The monty® 3550 blends traditional design elements with state-of-theart features to make the tire changing process more efficient, avoiding potential damage to the wheel. It is a superior solution for smallerscale high-volume shops in need of a versatile machine to service automobiles, SUVs, and light trucks. The on-floor bead breaker integrates with the tilt-tower configuration to facilitate effortless wheel placement, reducing technician fatigue and eliminating the potential for wheel damage.

SMARTSPEEDTM

Self-adjusting technology provides the optimum torque and maximizes the rotation speed for safe, efficient operation. This model can also be offered in a single-speed option. (115V without smartSpeedTM).

RIM CLAMPING BEAD SEATER

A direct burst of compressed air comes through the clamping jaws to facilitate bead seating.

PNEUMATIC BEAD PUSHER

Swift and ergonomically designed, this feature effectively accelerates the process of positioning the mounting head on all types of wheels.

ON-FLOOR BEAD BREAKER

A conventional side-shovel bead breaker, featuring an ergonomically positioned pedal control situated a small distance from the shovel, is the guickest solution for efficiently handling a range of tires.

TECHNICAL SPECIFICATIONS	
monty® 3550 (US)	M3550EM110B (115V 1Ph 60Hz)
monty® 3550 with smartSpeed® (US)	EEWH747B (230V 1Ph 60Hz)
monty® 3550 (CA)	EEWH786AUA (115V 1Ph 60Hz)
monty® 3550 with smartSpeed® (CA)	EEWH786AUB (230V 1Ph 60Hz)
Max Rim Diameter	26" 66cm
Max Tire Width	17" 43cm
Max Rim Width	16" 41cm
Max Wheel Diameter	47" 119cm
Air Pressure Required	116-174 PSI 8-12 bar
Dimensions HxWxD	58"x65"x90" 147x165x229cm

INNOVATIVE TIRE CHANGER FOR HIGH-VOLUME SHOPS

ADJUSTABLE CLAMPING JAWS



To safeguard the wheel's integrity, these nylon-covered jaws are selfcentering and grip the wheel firmly for elevated stability and safety.

TILT-TOWER



Utilizing a pneumatic design, this feature maximizes clearance for efficient placement of the tire onto the turntable.

PNEUMATIC EASYMONT®



Includes the top roller, pressing foot and lifting disk to streamline the mounting and demounting of low-profile and high-performance tires, enabling a single technician to perform tasks with ease.

TOOL BOX WITH INTEGRATED AIR PRESSURE GAUGE



Providing a secure storage space, the tool box includes four convenient shelves for the organization of tools, valves and accessories.

STANDARD ACCESSORIES

- · Wave Plus Tire Lever
- Plastic Rim Protector
- · Bead Breaker Blade Protector
- Lube Bucket
- · Lube Brush
- · Offset Mount/Demount Head Kit
- · Protective Insert for Mount/Demount Head

OPTIONAL ACCESSORY

• Wheel Lift (EAK0279G87A)





US 800.251.4500

CANADA 800.267.2185



