



SUPERIOR LEVERLESS TIRE CHANGER

 $\textbf{ENGINEERING UNLEASHED}^{\text{TM}}$

MAXIMUM SHOP PRODUCTIVITY AND SUPERIOR SERVICE QUALITY

The monty® 8700 smartSpeed™ from Hofmann® is a semi-automatic center post tire changer that stands out by employing an exceptional set of tools, minimizing effort and reducing the risk of potential damage when working with run-flat (RFT) and ultra-high-performance tires (UHP). It provides an innovative leverless mount/demount system, while smartSpeed™ technology assists in controlling the motor's optimum torque/speed combination to achieve peak performance. The dynamic dual-disk bead breaker can easily accommodate a diverse range of wheels, making the monty® 8700 a preferred solution for shops of all sizes. The monty® 8700 smartSpeed™ is the superior solution for professional shops with reputations built on efficient and precise tire-changing, especially with specialized tire types.



CENTER POST CLAMP

This design offers an array of essential benefits, with paramount importance placed on the significant reduction of potential wheel damage, as well as reduced clamping constraint in contrast to the turntable design.



SMARTSPEED™

This revolutionary, patent-protected technology optimizes the applied torque on the wheel and automatically establishes the maximum rotational speed of the wheel.



THE ULTIMATE IN PRODUCTIVITY AND PERFORMANCE

POWERMONTTM

This leverless mounting and demounting tool is designed to coordinate seamlessly with the dynamic bead breaker, ensuring optimal positioning. Engineered with upgraded steel and fortified plastic protection, its durability is unparalleled, even over the long term. This innovative system is ideally suited for a diverse range of tire types.



DYNAMIC BEAD BREAKER

The precisely calibrated synchronized dual-disk system thoroughly aligns both upper and lower tire beads, ensuring unparalleled precision and reducing the potential for wheel damage. Adjustable tilt feature included for tires with a stiff sidewall.





PNEUMATIC WHEEL LIFT

Utilizing pneumatic power, the pedal-operated wheel lift facilitates the lifting of heavy wheels, effectively minimizing technician fatigue and increasing overall productivity.



PNEUMATIC BEAD PUSHER

The Pneumatic Bead Pusher is designed with a reverse-side hook to assist in lifting heavy tires, efficiently facilitating the mounting process of the upper bead.

monty[®] 8700

OUTSTANDING SERVICE FOR PREMIUM PERFORMANCE TIRES





TOP-SIDE BEAD SEATER

This ergonomic precision tool quickly injects compressed air into a tire, ensuring the bead seals tightly onto the rim.



CONTROL PANEL

The user-friendly control panel employs a color-coded layout and tool-matching controls to ensure easy navigation.

TECHNICAL SPECIFICATIONS		
Air Pressure Required	116-174 PSI 8-12 bar	
Dimensions HxWxD	75"x63"x78" 190x160x198cm	
Max Rim Diameter	30" 76cm	
Max Rim Width	13" 33cm	
Max Tire Width	15" 38cm	
Max Wheel Diameter	47" 119cm	
Power Supply	230V 1ph 50-60Hz 16A	





https://hofmann-equipment.com/la-en/distributor



