

HOFMANN® 

monty® **3300-26 racing**

SMARTSPEED



RIM CLAMPING TYRE CHANGER

ENGINEERING UNLEASHED™

monty® 3300-26 racing

The monty® 3300-26 racing is a top-of-the-line tyre changer engineered to handle a wide range of OE tyre fitments for passenger cars and light trucks, making it the perfect choice for diverse applications.

With an extended clamping range and self-centring, adjustable clamping jaws, the monty® 3300-26 racing accommodates tyres ranging from 10 to 26 inches in diameter, with a maximum width of 15 inches and overall diameter of up to 44 inches.

The robust racing cabinet, lowered by two inches compared to standard models, delivers improved ergonomics when working with wide tyres.

The premium bead breaker shovel offers exceptional versatility with five adjustment axes for proper positioning, while the wide bead-breaker pad ensures maximum wheel stability during bead loosening.

Additionally, a top-side bead seater with a 24-litre tank promotes efficient tyre bead seating.

Our patented smartSpeed™ technology ensures high-speed turntable rotation and speed control with high torque output, guaranteeing safe, fast, easy, and efficient operation.

The easymont™ pneumatic bead assist optimises single technician use when mounting/demounting low-profile and high-performance tyres.


The updated easymont™ 330 pro features a new pressing tool optimised to prevent tool slippage that could damage tyres and wheels, with a reverse-side lifting hook, a hex roller and top roller bar, and lifting disk. The pressing tool can also be interchanged with a cone to help engage the jaw during clamping.

With its user-friendly design and advanced features, the monty® 3300-26 racing tyre changer promises superior performance and reliability for all your tyre-changing needs.



SMARTSPEED™

This revolutionary, patent-protected technology optimises the applied torque on the wheel and automatically establishes the maximum rotational speed of the wheel.



ADJUSTABLE CLAMPING JAWS

Four self-centring, three-way adjustable jaws provide a clamping range from 10 to 26 inches. Our system minimises cylinder stroke for faster clamping and features a compact turntable to reduce machine footprint.

**ROBUST VERSATILITY
HIGH THROUGHPUT
EASY TO USE**



TOP-SIDE BEAD
SEATER WITH
24L AIR TANK

TOOL BOX WITH
INTEGRATED AIR
PRESSURE GAUGE

WDK
ACCESSORIES

PNEUMATIC
VERTICAL ARM

EASYMONT™

NEW PRESSING
TOOL

ERGONOMIC BEAD
BREAKER PEDAL

SMARTSPEED™



ON-FLOOR BEAD BREAKER

Our premium on-floor bead breaker features a pedal-operated design for hands-free operation, a wide bead breaker pad for stability, and five shovel adjustment axes for precision. The high pad offset prevents interference between the tyre and the turntable cylinder, and the ergonomic pedal positioning enhances operator comfort.



EASYMONT™

Comprised of a new bead pressing tool with lifting hook, hex roller, top roller, and lifting disk, the new easymont™ 330 pro streamlines the mounting and demounting of low-profile and high-performance tyres, enabling a single technician to perform tasks with ease.



NEW PRESSING TOOL

The updated easymont™ 330 pro pneumatic bead assist features a new pressing foot style optimised to prevent tool slippage that could damage tyres and wheels.



FLEXION GUARD

The tilt-tower provides high rigidity with a reinforced horizontal arm that prevents flexions of the system when working on run-flat and high-performance tyres.



PNEUMATIC VERTICAL ARM

Ergonomically designed, this feature accelerates positioning the mounting head on all types of wheels.



TOP-SIDE BEAD SEATER

This precision tool quickly injects compressed air into the tyre, ensuring the bead seals tightly onto the rim.



TOOL BOX

Providing a secure storage space, the tool box includes four convenient shelves for the organisation of tools, valves and accessories.

TECHNICAL SPECIFICATIONS

Max Rim Diameter	26" 66cm
Max Tyre Width	15" 38cm
Max Rim Width	14" 35cm
Max Wheel Diameter	44" 112cm
Wheel Lift Capability (optional)	154 lbs. 70kg
Power Supply	230V 1ph 50-60Hz
Air Pressure Required	116-174 PSI 8-12 bar
Dimensions HxWxD	72"x63"x67" 182x159x171cm

VERSIONS

	racing GP PLUS	racing PLUS	racing GP	racing
easymont™ 330 pro	x	x	x	x
Top-side bead seater	x		x	
WDK accessories	x	x		
Conical roller bar	x	x		
Spacer chain	x	x		

FIND A DISTRIBUTOR

AUSTRIA
+43 2641 24524

FRANCE
+33 134 48 58 78

GERMANY
+49 8671 96200 0

ITALY
+39 0522 733 411



Snap-on® Total Shop Solutions offers a wide range of garage equipment solutions for workshops, garages, car dealers and tyre shops, thanks to the specific solutions provided by its portfolio of premium brands. Hofmann® is a brand of TSS and is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2025 Snap-on Incorporated. Hofmann® is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All other marks are marks of their respective holders. sswzh23039a (EU en) 09/2025



HOFMANN-EQUIPMENT.COM

HOFMANN®